



J COLORS S.p.A.

New wood flatting

Divisione TOSCANO
Revision nr.4
Dated 22/04/2010
Printed on 02/05/2010
Page n. 1 / 4

Safety Data Sheet

1. Identification of the substance / preparation and the Company

1.1 Identification of the substance or preparation

Product name New wood flatting

1.2 Use of the substance / preparation

Intended use Flattening varnish for wood

1.3 Company identification

Name J COLORS S.p.A.
Full address VIA SETTEMBRINI, 39
District and Country 20020 LAINATE MI
ITALIA
Tel. +39 02 937541
Fax +39 02 93754274

e-mail address of the competent person responsible for the Safety Data Sheet lab@jcolors.com

Product distribution by Laboratorio J Colors S.p.A
+39 02 93754222/243

1.4 Emergency telephone

For urgent inquiries refer to Centro Antiveleni Milano
Niguarda +39 02 66101029

2. Hazards Identification

2.1 Substance/Preparation Classification

This product is not dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Nevertheless, this preparation contains dangerous substances in concentrations that must be declared in section No. 3 and requires a safety data sheet containing all the information required under the Regulation (EC) 1907/2006 and subsequent amendments.

3. Composition / Information on ingredients

Contains:

Name	Concentration % (C)	Classification
2-(2-BUTOXYETHOXY)ETHANOL	1,90<= C <3,00	
C.A.S. number 112-34-5		
EC number 203-961-6		
INDEX number 603-096-00-8		
<i>Substance with a community workplace exposure limit.</i>		

4. First aid measures

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.

INHALATION: Remove to open air. If breathing is irregular, seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SUITABLE EXTINGUISHING MEDIA



J COLORS S.p.A.

New wood flatting

Divisione TOSCANO
Revision nr.4
Dated 22/04/2010
Printed on 02/05/2010
Page n. 2 / 4

The extinction equipment should be of the conventional kind: carbon dioxide, foam, powder and nebulised water.

EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS

None in particular.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and dielectric), a depressurised mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event of large quantities of foam.

6. Accidental release measures

PERSONAL PRECAUTIONS

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. If there are no contraindications, spray solid products with water to prevent the formation of dust. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, see the other sections of this sheet.

ENVIRONMENTAL PRECAUTIONS

The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

METHODS FOR CLEANING UP

Use inert absorbent material (sand, vermiculite, diatomaceous earth, Kieselguhr, etc.) to soak up leaked product. Collect the majority of the remaining material and deposit it in containers for disposal. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

7. Handling and storage

Store in a well ventilated place, keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, bright flames and sparks and other sources of ignition.

8. Exposure control / personal protection.

8.1 Exposure limit values

Product name	Type	Country	TWA/8h		STEL/15min		
			mg/m ³	ppm	mg/m ³	ppm	
2-(2-BUTOXYETHOXY)ETHANOL	OEL	EU	67,5	10	101,2	15	Skin

8.2 Exposure controls

Observance of safety measures used in handling chemical substances.

RESPIRATORY PROTECTION

If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

EYE PROTECTION

None required.

HAND PROTECTION

None required.

SKIN PROTECTION

None required.

9. Physical and chemical properties

Colour	Clear
Odour	Ammoniacal
Appearance	Liquid
Solubility	Water-soluble
Viscosity	80-85 KU
Vapour density	Not available
Evaporation Rate	Not available
Reactive Properties	Not available
Partition coefficient: n-octanol/water	Not available
pH	> 8,5
Boiling point	Not available



J COLORS S.p.A.

New wood flatting

Divisione TOSCANO
Revision nr.4
Dated 22/04/2010
Printed on 02/05/2010
Page n. 3 / 4

Flash point	>	61	°C	
Explosive properties		Not available		
Vapour pressure		17,20	a 20° C	
Specific gravity		1,050	Kg/l	
Solid content:		41,29%		
VOC (Directive 2004/42/EC) :		5,39%	-	56,59
VOC (volatile carbon) :		2,89%	-	30,34

g/litre of preparation
g/litre of preparation

10. Stability and reactivity

The product is stable in normal conditions of use and storage. Due to thermal decomposition or in the event of a fire vapours may be produced potentially dangerous to health.

Diethylene glycol butyl ether may react with oxidizing agents. When heated to decomposition, it emits acrid and irritant fumes. It is hygroscopic.

Propylene glycol: it is hygroscopic, stable at normal conditions; at high temperatures, it tends to oxidize yielding propionaldehyde as well as lactic and acetic acid.

11. Toxicological information

Butyl diglycol: can be absorbed by inhalation, ingestion and skin contact; it is irritant to the skin and especially to the eyes; spleen damage may occur. Inhalation is unlikely to occur at room temperature due to the low vapour tension of the substance.

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

13. Disposal consideration

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

This substance is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15. Regulatory information

Warning symbols: None
Hazard sentences (R): None
Caution recommendations (S): None
Safety data sheet available upon request for professional users.

Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.

VOC (Directive 2004/42/EC) :

Interior/exterior trim varnishes and woodstains, including opaque woodstain.

VOC given in g/litre of product in a ready-to-use condition :

Limit value:	150 (2007) - 130 (2010)	VOC of product :	51,45
- Thinned with :	10,00% WATER		

16. Other information

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments;
2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX);
3. Regulation (EC) 1272/2008 (CLP) of the European Parliament;
4. Regulation (EC) 1907/2006 (REACH) of the European Parliament;
5. The Merck Index. - 10th Edition;
6. Handling Chemical Safety;
7. Niosh - Registry of Toxic Effects of Chemical Substances;



J COLORS S.p.A.

New wood flatting

Divisione TOSCANO
Revision nr.4
Dated 22/04/2010
Printed on 02/05/2010
Page n. 4 / 4

8. INRS - Fiche Toxicologique (toxicological sheet);
9. Patty - Industrial Hygiene and Toxicology;
10. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review

The following sections were modified:

08/13