



## Safety Data Sheet

### 1. Identification of the substance / preparation and the Company

#### 1.1 Identification of the substance or preparation

Product name Morgan's primer antiruggine glicero ftalica

#### 1.2 Use of the substance / preparation

Intended use Synthetic antirust paint

#### 1.3 Company identification

Name J COLORS S.p.A.  
Full address VIA SETTEMBRINI, 39  
District and Country 20020 LAINATE MI  
ITALIA  
Tel. +39 02 937541  
Fax +39 02 93754274

e-mail address of the competent person responsible for the Safety Data Sheet lab@jcolors.com

Product distribution by Laboratorio J Colors S.p.A  
+39 02 93754222/243

#### 1.4 Emergency telephone

For urgent inquiries refer to Centro Antiveleni Milano  
Niguarda +39 02 66101029

### 2. Hazards Identification

#### 2.1 Substance/Preparation Classification

This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this product requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: N  
R phrases: 10 - 50/53

#### 2.2 Danger Identification

Because of its chemical-physical features, this product is graded as flammable (flash-point 21 °C or higher and 55 °C or lower ).  
VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.  
This product contains sensitizing substance/s and may cause allergic reactions.

### 3. Composition / Information on ingredients

Contains:

Name	Concentration % (C)	Classification
<b>AMINES, N-TALLOW ALKYLTRIMETHYLENE-DI, OLEATES</b>	0,25<= C <0,30	C R34 N R50
C.A.S. number 61791-53-5 EC number 263-186-4		
<b>ZINC PHOSPHATE TETRAHYDRATE</b>	3,90<= C <5,00	N R51/53
C.A.S. number 7779-90-0 EC number 231-944-3		
<b>ZINC OXIDE</b>	0,10<= C <0,15	N R50/53
C.A.S. number 1314-13-2 EC number 215-222-5 INDEX number 030-013-00-7		



# J COLORS S.p.A.

## Morgan's primer antiruggine glicero ftalica

Divisione TOSCANO  
Revision nr.5  
Dated 03/10/2008  
Printed on 02/05/2010  
Page n. 2 / 5

<b>XYLENE (MIXTURE OF ISOMERS)</b>	0,6999<= C <0,8999	Xn	R20/21	
<i>C.A.S. number</i>	1330-20-7	Xn	R65	
<i>EC number</i>	215-535-7	Xi	R38	
<i>INDEX number</i>	601-022-00-9		R10	
			Note	C
<b>1,2,4-TRIMETHYLBENZENE</b>	0,30<= C <0,35	Xn	R20	
<i>C.A.S. number</i>	95-63-6	Xi	R36/37/38	
<i>EC number</i>	202-436-9		R10	
<i>INDEX number</i>	601-043-00-3	N	R51/53	
<b>NAPHTA (PETROL.) HYDRODESULFURIZED HEAVY</b>	17,00<= C <20,00	Xn	R65	
<i>C.A.S. number</i>	64742-82-1		R10	
<i>EC number</i>	265-185-4		R66	
<i>INDEX number</i>	649-330-00-2	N	R51/53	
			Note	H P 4

The complete text of -R- phrases is specified in section 16.

#### 4. First aid measures

**EYES:** Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

**SKIN:** Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.

**INHALATION:** Remove to open air. If breathing is irregular, seek medical advice.

**INGESTION:** Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

#### 5. Fire-fighting measures

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Excess pressure may form in containers exposed to fire at a risk of explosion. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SUITABLE EXTINGUISHING MEDIA

The extinction equipment to be used is the conventional kind: carbon dioxide, foam, powder and nebulised water.

##### EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist) work gloves (fireproof, cut proof and dielectric), self-respirator (self-protector).

#### 6. Accidental release measures

##### PERSONAL PRECAUTIONS

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. If there are no contraindications, spray solid products with water to prevent the formation of dust. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, see the other sections of this sheet.

##### ENVIRONMENTAL PRECAUTIONS

The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

##### METHODS FOR CLEANING UP

Use inert absorbent material (sand, vermiculite, diatomaceous earth, Kieselguhr, etc.) to soak up leaked product. Collect the majority of the remaining material and deposit it in containers for disposal. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 7. Handling and storage

Store in a well ventilated place, keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, bright flames and sparks and other sources of ignition.



# J COLORS S.p.A.

## Morgan's primer antiruggine glicero ftalica

Divisione TOSCANO  
Revision nr.5  
Dated 03/10/2008  
Printed on 02/05/2010  
Page n. 3 / 5

### 8. Exposure control / personal protection.

#### 8.1 Exposure limit values

Product name	Type	Country	TWA/8h		STEL/15min		
			mg/m3	ppm	mg/m3	ppm	
ZINC OXIDE	TLV-ACGIH		2	0,6	10	3	
	OEL	IRL	5		10		
XYLENE (MIXTURE OF ISOMERS)	TLV-ACGIH		434	100	651	150	Skin
	OEL	EU	221				Skin
	OEL	IRL		50		100	Skin
	WEL	UK		50		100	Skin
1,2,4-TRIMETHYLBENZENE	TLV-ACGIH		123	25			Skin
	OEL	EU	100				Skin
	OEL	IRL		20			Skin
	WEL	UK		25			Skin
NAPHTA (PETROL.) HYDRODESULFURIZED HEAVY	TLV (ACGIH)		575				

TLV of solvent mixture: 402,000 mg/m3

#### 8.2 Exposure controls

In order to minimize exposure as far as possible, it is strongly recommended to use adequate individual protective measures, such as: masks suitable for the product, goggles, gloves and overall. Do not eat, drink or smoke while handling it. Wash hands accurately with soap and water before meals and at the end of the work shift.

### 9. Physical and chemical properties

Colour	Grey
Odour	Aromatic
Appearance	Liquid
Solubility	Insoluble in water
Viscosity	120'-140'CF4
Vapour density	Not available
Evaporation Rate	Not available
Reactive Properties	Not available
Partition coefficient: n-octanol/water	Not available
pH	Not available
Boiling point	Not available
Flash point	> 21 °C
Explosive properties	Not available
Vapour pressure	1,65 a 20° C
Specific gravity	1,500 Kg/l
Solid content:	77,48%
VOC (Directive 2004/42/EC) :	22,26% - 333,90 g/litre of preparation
VOC (volatile carbon) :	18,46% - 276,90 g/litre of preparation

### 10. Stability and reactivity

The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbon oxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.

Calcium carbonate: avoid contact with acids.

### 11. Toxicological information

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This product may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

### 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it may even have negative effects on aquatic environment.

AMINES, N-TALLOW ALKYLTRIMETHYLENE-DI, OLEATES  
LC50 (96h) 1 mg/l



# J COLORS S.p.A.

## Morgan's primer antiruggine glicero ftalica

Divisione TOSCANO  
Revision nr.5  
Dated 03/10/2008  
Printed on 02/05/2010  
Page n. 4 / 5

EC50 (48h) 0,01 mg/l  
IC50 (72h) 0,1 mg/l

ZINC OXIDE  
LC50 (96h) 1,1 mg/l Oncorhynchus mykiss  
EC50 (48h) 1.000 mg/l Daphnia magna

### 13. Disposal consideration

Consider the possibility of burning the product in a suitable incenerator.

Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

### 14. Transport information

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

#### Road and rail transport:

ADR/RID Class:	3	UN: 1263
Packing Group:	III	
Label:	3	
Nr. Kemler:	30	
Special Provision:	640E	
Proper Shipping Name:	Paint or paint related material	



#### Carriage by sea (shipping):

IMO Class:	3	UN: 1263
Packing Group:	III	
Label:	3	
EMS:	F-E, S-E	
Marine Pollutant		
Proper Shipping Name:	Paint or paint related material	



#### Transport by air:

IATA:	3	UN: 1263
Packing Group:	III	
Label:	3	
Cargo:		
Packaging instructions:	310	Maximum quantity: 220 L
Pass.:		
Packaging instructions:	309	Maximum quantity: 60 L



### 15. Regulatory information



DANGEROUS FOR THE ENVIRONMENT

<b>R10</b>	FLAMMABLE.
<b>R50/53</b>	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>S 2</b>	KEEP OUT OF THE REACH OF CHILDREN.
<b>S23</b>	DO NOT BREATHE GAS/FUMES/VAPOUR/SPRAY
<b>S29</b>	DO NOT EMPTY INTO DRAINS.
<b>S46</b>	IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.
<b>S51</b>	USE ONLY IN WELL-VENTILATED AREAS.
<b>S61</b>	AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS.

Contains:

2-BUTANONE OXIME

May cause allergic reactions.

Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.

VOC (Directive 2004/42/EC) :

One-pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :

Limit value:	600 (2007) - 500 (2010)	VOC of product :	406,69
- Thinned with :	10,00%	DILUENTE PER SINTETICI ALIF.	



# J COLORS S.p.A.

## Morgan's primer antiruggine glicero ftalica

Divisione TOSCANO  
Revision nr.5  
Dated 03/10/2008  
Printed on 02/05/2010  
Page n. 5 / 5

### 16. Other information

Text of -R- phrases quoted in section 3 of the sheet.

<b>R34</b>	CAUSES BURNS.
<b>R50</b>	VERY TOXIC TO AQUATIC ORGANISMS.
<b>R51/53</b>	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>R50/53</b>	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>R20/21</b>	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
<b>R65</b>	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
<b>R38</b>	IRRITATING TO SKIN.
<b>R10</b>	FLAMMABLE.
<b>R20</b>	HARMFUL BY INHALATION.
<b>R36/37/38</b>	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
<b>R66</b>	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

#### GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments;
2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX);
3. Regulation (EC) 1272/2008 (CLP) of the European Parliament;
4. Regulation (EC) 1907/2006 (REACH) of the European Parliament;
5. The Merck Index. - 10th Edition;
6. Handling Chemical Safety;
7. Niosh - Registry of Toxic Effects of Chemical Substances;
8. INRS - Fiche Toxicologique (toxicological sheet);
9. Patty - Industrial Hygiene and Toxicology;
10. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition;

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

#### Changes to previous review

The following sections were modified:

02/09/12/15