

**ADDITIVO OPACANTE PER NEW LACK E NEW WOOD
FLATTING B-02
DULLING ADDITIVE FOR NEW LACK AND NEW WOOD
FLATTING**



PROPERTIES

Paste for dulling water-based NEW LACK enamel and water-based NEW WOOD FLATTING varnish. The additive gives enamel a pleasant and even satin finish without compromising its outdoor resistance.

COATING SYSTEM

To achieve the satin effect, add one 85ml bottle of ADDITIVO OPACANTE dulling agent for every 750 ml of product to be dulled.

For the 2.5-litre container, add three 85ml bottles of ADDITIVO OPACANTE dulling agent.

WARNINGS

Stir before use. Stir the enamel and/or flattening varnish well after adding the additive. Keep tin tightly sealed, upside down, at a temperature over +5 °C.

TENDER SPECIFICATION ITEM

Application of NEW LACK, a blend of non-yellowing acrylic resin and resistant pigments, in two coats to a thickness of 25 microns each, on suitably prepared substrates.

MAIN DATA AT 20°C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l =		Thinner THINNER		Equipment cleaning =		Roller application =	
Appearance and finish =		Dust dry =		Specific weight kg/l =		Brush application =	
Colours =		Touch dry after =		Solids by volume =		Knife application =	
Exterior / interior use =		Through drying after =		Viscosity =		Air assisted spraying =	
Shelf life =		Overcoating interval =		Flash point =			

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

J COLORS S.p.A.

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230