

PASTA OPACANTE PER MORGAN'S FAST **B-27**
DULLING PASTE FOR MORGAN'S FAST
Dulling paste for fast-drying enamel



PROPERTIES

Paste for dulling fast-drying enamel MORGAN'S FAST.

The additive gives enamel a pleasant and even satin finish without compromising its outdoor resistance.

APPLICATION INSTRUCTIONS

Once you have got the right colour in the gloss finish using the PROGRESS TONATONE colour matching system, to achieve the mat finish, add an amount of PASTA OPACANTE PER MORGAN'S FAST dulling paste varying between 5% and 20% (at most) depending on the desired degree of gloss.

Stir MORGAN'S FAST enamel well after adding the additive.

The dulling product must be thinned at 10% less than the doses given on the gloss MORGAN'S FAST technical product sheet.

WARNINGS

Keep tin tightly sealed, upside down, in a cool place away from heat sources.

MAIN DATA AT 20°C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l =		Thinner =		Equipment cleaning =		Roller application =	
Appearance and finish =		Dust dry =		Specific weight kg/l =		Brush application =	
Colours =		Touch dry after =		Solids by volume =		Knife application =	
Exterior / interior use =		Through drying after =		Viscosity =		Air assisted spraying =	
Shelf life 12 MONTHS		Overcoating interval =		Flash point =			

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

J COLORS S.p.A.

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230