

MORGAN'S STUCCO IN PASTA D-11
MORGAN'S PASTE STUCCO
 Filler in paste for wood and walls



PROPERTIES

Filler in paste for walls and wood, with high filling power. Particularly suitable for levelling small surface areas and for sealing holes and cracks. Can be painted over with emulsion paints, and synthetic solvent- and water-based enamels, applied with a brush.

COATING SYSTEM

Apply the product in thin, even layers with a suitable metal knife.

In order to avoid uneven gloss levels and other defects owing to absorption differing between the substrate and repaired areas, we recommend you seal the surface to be painted with WUNDER FLEX, MORGAN'S FLEX or PONTE DI ANCORAGGIO For premixed surfaces, use PONTE DI ANCORAGGIO only.

WARNINGS

Affected by freezing temperatures. Keep at a temperature over +5 °C in a tightly sealed tin away from heat sources.

MAIN DATA AT 20 °C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l =		Thinner =		Equipment cleaning SOAP AND WATER		Roller application =	
Appearance and finish MAT		Dust dry =		Specific weight kg/l 1.9		Brush application =	
Colours WHITE		Touch dry after =		Solids by volume =		Knife application READY PRODUCT	
Exterior / interior use NO/YES		Through drying after 2-4 HOURS		Viscosity CREAMY		Air assisted spraying =	
Shelf life 24 MONTHS		Overcoating interval 3-5 HOURS		Flash point =			

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

J COLORS S.p.A.

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230