

BIOSAN 1 E-02

Restorative solution for walls



PROPERTIES

Detergent solution for walls, powerful disinfectant, effectively cleans and disinfests walls.

Ready product.

Recommended before applying emulsion paints or wallpaper in rooms where there is a lot of water vapour.

COATING SYSTEM

Remove any traces of old paintwork that are flaking off or efflorescing.

Brush the product directly onto walls to be disinfested after thinning with water at 50%.

After 2 – 3 hours, remove efflorescence with a brush.

Repeat the operation if incrustations persist.

Walls remain impregnated with the active substances for a long time, producing an effective protective action.

After 5 - 6 hours, finish with two coats of BIOSAN 2 LUCIDO or BIOSAN 2 OPACO.

WARNINGS

Do not apply when temperature of the air, substrate or product is below +5 °C. Do not apply on surfaces that are warm or exposed to sunlight. Keep in tightly sealed tin, at a temperature over +5 °C.

MAIN DATA AT 20 °C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l		Thinner		Equipment cleaning		Roller application	
10		WATER		WATER		=	
Appearance and finish		Dust dry		Specific weight kg/l		Brush application	
MAT		=		1		50% WATER	
Colours		Touch dry after		Solids by volume		Knife application	
CLEAR		=		=		=	
Exterior / interior use		Through drying after		Viscosity		Air assisted spraying	
NO/YES		=		10''FORD 4		=	
Shelf life		Overcoating interval		Flash point			
24 MONTHS		5-6 HOURS		=			

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

J COLORS S.p.A.

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230