

MUFFA STOP E-04
MILDEW STOP
 Fungicidal additive for emulsion paints



PROPERTIES

Wide-ranging fungicidal additive, suitable for preventing and stopping mould growth developing in the home.

APPLICATION INSTRUCTIONS

Stir MUFFA STOP well before use. Slight separation of the liquid is normal and does not alter the product's effectiveness.

Pour MUFFA STOP into the emulsion paint before the paint is thinned. Note that the product is at its most effective when stirred well (one 250ml pack of MUFFA STOP for every 3 litres of emulsion paint).

Thin the emulsion paint following the manufacturer's instructions, and stir well.

WARNINGS

Keep in tightly sealed tin, at a temperature over +5°C but no more than +35 °C.

To use all the product, wash the empty container with water and use the resulting mixture to thin the emulsion paint.

MAIN DATA AT 20 °C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l		Thinner		Equipment cleaning		Roller application	
Appearance and finish		Dust dry		Specific weight kg/l	1.4 	Brush application	
Colours		Touch dry after		Solids by volume		Knife application	
Exterior / interior use		Through drying after		Viscosity	8000 cps. 	Air assisted spraying	
Shelf life	24 MONTHS 	Overcoating interval		Flash point	= 		

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

J COLORS S.p.A.

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230