

# CONTACT F-11

## Clear emulsion paint for interior use



### PROPERTIES

Breathable emulsion paint, ideal for bathrooms and kitchens, with high opacity and excellent white point. An excellent finish is guaranteed. Easy to apply, mat velvet finish.

### COATING SYSTEM

#### SURFACE PREPARATION

**Standard plaster:** allow to dry out, clean any dirt stains.

**Water-based paintwork and varnishes:** if sound, dry clean or wash; otherwise, eliminate completely and wash with water.

**Limewash or silicate paintwork:** eliminate completely and dust.

**Mouldy walls:** after cleaning, restore with BIOSAN 1.

Fill with MORGAN'S STUCCO IN PASTA or IN POLVERE.

**Apply a coat of sealer**, taking care to choose the one most suitable for the kind of substrate, MORGAN'S FLEX, WUNDER FLEX, FISSATIVO, PONTE DI ANCORAGGIO. For premixed surfaces, apply a coat of odourless solvent-based sealer PONTE DI ANCORAGGIO only.

#### FINISH

Allow to dry thoroughly. Apply two coats of CONTACT, leaving approx. 4 -5 hours between coats.

### WARNINGS

Do not apply when temperature of the air, substrate or product is below +5 °C. Keep in tightly sealed tin, at a temperature over +5°C.

#### TENDER SPECIFICATION ITEM

Brush, roller or spray application of CITY, breathable emulsion paint for interior use, formulated with a blend of vinylversatic resin, titanium-dioxide and calcium carbonate.

MAIN DATA AT 20 °C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l		Thinner		Equipment cleaning		Roller application	
12		WATER		WATER		30-40 % WATER	
Appearance and finish		Dust dry		Specific weight kg/l		Brush application	
MAT		=		1.6		30-40% WATER	
Colours		Touch dry after		Solids by volume		Knife application	
WHITE AND PROGRESS TONATONE		2-3 HOURS		=		=	
Exterior / interior use		Through drying after		Viscosity		Air assisted spraying	
NO/YES		12 HOURS		45000 cps.		40 % WATER	
Shelf life		Overcoating interval		Flash point		NOZZLE DIAM. 1.5 -1.7 mm PRESSURE 2.5 -3 atm AIRLESS NOZZLE DIAM. 0.66 mm PRESSURE 100 -200 atm	
24 MONTHS		4-5 HOURS		=			

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

**J COLORS S.p.A.**

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230