

CONTRO L'UMIDITA' G-05
ANTI-HUMIDITY
Restorative masonry paint for interior use



PROPERTIES

Restorative masonry paint for damp walls, formulated with a blend of acrylic resin and calcium silicates. Ideal for preventing damp patches appearing in homes, it controls how much moisture contained in the wall is let out.

COATING SYSTEM

SURFACE PREPARATION

Standard plaster: allow to dry out, clean any dirt stains.

Water-based paintwork and varnishes: eliminate completely and wash with water.

Limewash or silicate paintwork: eliminate completely and dust.

Mouldy walls: after cleaning, restore with BIOSAN 1. Allow to dry thoroughly.

FINISH

Can be applied with brush or roller on substrate previously dampened with water.

Apply two or three coats to a good thickness, leaving 12 hours between coats (apply at least 500 ml/sq m).

WARNINGS

Apply on damp walls. Do not apply on warm surfaces. Do not apply when temperature of the air, substrate or product is below +5 °C.

TENDER SPECIFICATION ITEM

Application of two or three coats of CONTRO L'UMIDITA' on walls prone to damp. Product formulated with a blend of acrylic resin and calcium silicates combined to reduce capillary pressure of water inside walls and to prevent salt and fungal patches from forming.

MAIN DATA AT 20 °C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l		Thinner SYNTHETIC THINNER		Equipment cleaning SYNTHETIC THINNER		Roller application 3-5% SYNTHETIC THINNER	
6							
Appearance and finish		Dust dry		Specific weight kg/l		Brush application 3-5% SYNTHETIC THINNER	
MAT		30'		1.53			
Colours		Touch dry after		Solids by volume		Knife application	
WHITE		2 HOURS		51		=	
Exterior / interior use		Through drying after		Viscosity		Air assisted spraying	
NO/YES		24 HOURS		CREAMY		=	
Shelf life		Overcoating interval		Flash point			
12 MONTHS		12 HOURS		37°C			

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

J COLORS S.p.A.

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230