

RINASCIMENTO CALCE NATURALE A SPATOLA L-03
RENAISSANCE SPATULA NATURAL LIME
Decorative stucco formulated with calce bicarbonata and additives



PROPERTIES

Decorative stucco formulated with a blend of slow-process pure hydrated lime, natural earth, and non film-forming additives in powder. Excellent transpirability. Particularly recommended for decorating exterior and interior walls. Impervious to mould, fungal and bacterial growth.

Can be coloured with inorganic universal colorants.

COATING SYSTEM

SURFACE PREPARATION

Erect scaffolding so as to make application as easy and continuous as possible right up to breaks in the structure (stringcourses, gaps, corners).

Old plaster or plaster patched up with old paintwork: remove paintwork, and any fungi and mould.

Clean thoroughly with a water buffing machine.

New fresh or dried out plaster: apply RINASCIMENTO CALCE NATURALE A SPATOLA directly.

Premixed surfaces: sand repair areas and rough casting edges, clean dirt stains, apply a coat of PONTE DI ANCORAGGIO. Given the considerable amount of premixed surfaces on the market, we strongly recommend you perform trials on small surface areas before going ahead with final application.

FINISH :Apply two levelling coats on the damp surface with RINASCIMENTO CALCE NATURALE A SPATOLA, sanding between coats until the surface is perfectly smooth. Leave at least 6 hours between coats.

Next, use a stainless steel trowel to apply several "chipping" coats in a crisscross pattern. Allow the product applied to dry for a few minutes before polishing with repeated strokes of the trowel on its edge, only applying measured pressure on the last coat.

For a greater gloss finish, apply natural beeswax on the surface once dry.

WARNINGS

Do not apply on warm surfaces exposed to sunlight. Keep out of the rain for at least two or three days.

Keep eyes protected whilst applying. In case of contact, wash with plenty of water.

Lighter and darker variations in shade are typical of the product. Use the same production batch for the same job. Do not apply on compact, prestressed or premixed concrete substrates. If colours have been produced with a tinting machine, mix with a drill fitted with a suitable propeller.

TENDER SPECIFICATION ITEM

Application of RINASCIMENTO CALCE NATURALE A SPATOLA decorative stucco, formulated with a blend of lime, non film-forming additives accounting for less than 5%, and natural earth, on suitably prepared substrates.

MAIN DATA AT 20 °C AND 70 % RELATIVE HUMIDITY

Theoretical spreading rate Per coat sq m/l 1,6-3		Thinner WATER		Equipment cleaning WATER		Roller application =	
Appearance and finish GLOSS		Dust dry =		Specific weight kg/l 1.55		Brush application =	
Colours WHITE AND PROGRESS TONATONE		Touch dry after 5-6 HOURS		Solids by volume =		Knife application READY PRODUCT	
Exterior / interior use YES/YES		Through drying after 24 HOURS		Viscosity CREAMY		Air assisted spraying =	
Shelf life 6 MONTHS		Overcoating interval 6 HOURS		Flash point =			

As conditions and feasibility of use may be influenced by external factors beyond the manufacturer's control, the Company declines all responsibility for results.

J COLORS S.p.A.

Via Settembrini, 39 - 20020 Lainate (MI) - Italy - Tel. ++ 39 02 937541 - Fax ++ 39 02 9374114

EDITION 6/ 99 1230